

County of Fresno

DEPARTMENT OF PUBLIC WORKS AND PLANNING ALAN WEAVER, DIRECTOR

GUIDELINES FOR DISPOSING OF NON-FRIABLE ASBESTOS AT AMERICAN AVENUE DISPOSAL SITE

- 1. The following information must be submitted in writing to the Fresno County Department of Public Works and Planning, Resources Division, 2220 Tulare Street, 6th Floor, Fresno, CA 93721, Attention: Mike Belman, Senior Engineering Technician; Phone: (559) 600-4259 or FAX: (559) 600-4552:
 - A. Material Analysis Report from a Certified Laboratory to include the following:
 - 1) Client Specimen Identification Number;
 - 2) Location of Removal of Specimen; (i.e., Fresno High School, etc.);
 - 3) Specimen Description (i.e., roofing material, black, etc.);
 - 4) Type of Asbestos Detected (i.e., Percent Actinolite, Percent Chrysotile, etc.);
 - 5) Specimen Composition (i.e., Percent Synthetic Fiber, Percent Minerals, Percent Binder, etc.);
 - 6) Test Method Used, (i.e., TPM, etc.);
 - 7) Identify laboratory CAL OSHA Number. (if applicable); and
 - 8) Identify laboratory certification number.
 - B. A letter stating that subject material is non-friable asbestos. Letter must be signed by a California Certified Asbestos Consultant or Certified Industrial Hygienist and include his/her certification expiration date.
- 2. After the County receives the above letter and lab report, not less than five working days will be required to analyze the information

Non-Friable Asbestos Guidelines Page 2

After the required five working days, approval or denial will be forwarded in writing from the Resources Division to the Contractor (NOTE: NO LESS THAN 24 HOURS NOTICE MUST BE GIVEN BY THE CONTRACTOR TO THE RESOURCES DIVISION PRIOR TO UTILIZING THE AMERICAN AVENUE DISPOSAL SITE.) This document must accompany the load of non-friable asbestos, along with a copy of the Material Analysis Report and letter from the certified laboratory. These documents must be given to the Scale Attendant at the disposal site prior to unloading each delivery of non-friable asbestos.

- 3. Non-friable asbestos loads will not be accepted at the American Avenue Disposal Site after 1:00 P.M.
- 4. The required packaging of the non-friable asbestos prior to disposal shall be as follows: *Must be completely "burrito" wrapped in 10 ml (or greater) clear plastic and secured with duct tape or by similar means* in such a manner that no material from the load will be exposed during the unloading and disposal process.
- 5. NO OTHER REFUSE WILL BE ALLOWED IN CERTIFIED NON-FRIABLE ASBESTOS LOADS.

PLEASE NOTE: FAILURE TO COMPLY WITH ANY OF THE ABOVEMENTIONED REQUIREMENTS IS GROUNDS FOR REJECTION OF THE CURRENT LOAD, AND POSSIBLE FUTURE LOADS OF NON-FRIABLE ASBESTOS MATERIAL.

G:\4360Resources\Disposal Sites\Asbestos\Asbestos Program\Guidelines\AsbestosDisposal Guidelines 2-22-13.doc